

# Sea Tel Model 9711 TxRx

3-Axis marine stabilized antenna system compatible with C- or Ku-band satellites

2013 Data Sheet

**COBHAM**

The most important thing we build is trust

## Model 9711 TxRx

The Sea Tel 9711 system with 2.4m radical offset reflector is our most efficient C-band or Ku-band marine stabilized antenna system. It is Intelsat approved. The 9711 is available in 144" or 168" radome.

The C-band configuration of the 9711 antenna system operates on C-band A Pol, C-band B Pol or C-band linear all controlled from the DAC 2202. This eliminates the need for a technician to climb into the radome and manually change the feed. The switch over from one polarization to

another can be accomplished in less than one minute.

The Sea Tel 9711 Ku-band system works with co polarized (co pol) or cross polarized (X pol) services which are also remotely selectable.

The Sea Tel 9711 system is fully compatible with OpenAmip, ROAM and Automatic Beam Switching (ABS) technologies. By combining multiple option files in a single modem, the user can make near seamless transitions from C-band circular A Pol to

B Pol to C-band linear or from Ku-band co pol to cross pol.

The 9711 technology uses Generation 2 electronics in the pedestal control unit. This is the same reliable electronics used on XX09MK2 and XX10 series antenna systems, eliminating an external level cage, and combines the software-controlled motor driver assembly for better diagnostics and improved troubleshooting capabilities on all 3 axes.

## Features and Benefits

- For C-band: circular/linear selectable feed allows automatic switch-over from circular to linear operation.
- For Ku-band: operate on co pol or X pol satellites.
- Fast switching time between networks: less than 1 minute.
- Fully compatible with OpenAmip, ROAM, and ABS protocol.
- Designed to meet MIL-STD-167 specifications for shock and vibration.
- Designed to meet Navy MIL-STD-901D Grade B shock standards and MIL-STD-461 EMI & RFI standards (including 200V/M).
- Fast satellite acquisition using built-in GPS antenna and proprietary algorithms.
- High performance stabilization and satellite targeting, including inclined orbit satellites.
- Available with air conditioner (optional).




Sea Tel 9711 with Ku-band feed.

# Sea Tel Model 9711 TxRx

3-Axis marine stabilized antenna system compatible with C- or Ku-band satellites



Sea Tel 9711 with C-band feed.



## Typical data for Model 9711 TxRx

System Characteristics		
<b>Radome Dimensions</b>	3.66m/144in D x 4.17m/164in H	
<b>Pedestal Type</b>	3 Axis: Azimuth, Elevation, and Cross Level	
<b>Designed to Meet</b>	MIL STD 167-1, MIL-STD-901D and MIL-STD-461	
<b>Response Rate</b>	>100°/sec	
<b>Stabilization Accuracy</b>	0.1° (RMS)	
<b>Ship's Motion</b>	+/- 25° roll or +/- 25° pitch	
	C-Band	Ku-Band
<b>Antenna</b>	94" (2.4m) offset	94" (2.4m) offset
<b>Feed Assembly</b>	C-band circular/linear selectable	Ku-band linear polarized (XP, Co pol)
<b>Frequency Range</b>	Rx: 3.4-4.2 GHz Tx: 5.850-6.725 GHz	Rx: 10.7-12.75 GHz Tx: 13.75-14.5 GHz
<b>G/T</b>	20.2dB/K (calculated) @ 3.95 GHz	28.2 dB/k (calculated) @ 11.85 GHz
<b>Antenna Gain</b>	Receive: 38.5 dBi @ 3.95 GHz Transmit: 41.7 dBi @ 6.18 GHz	Receive: 47.75 dBi @ 11.85 GHz Transmit: 48.45 dBi @ 14.25 GHz
<b>Elevation Range</b>	-15 to +100°	
<b>Azimuth Range</b>	Unlimited	

## Typical data for DAC 2202 Controller

- Model DAC 2202
- Mounting Rack: optional slides
- M&C Ports: 1 Serial, 3 TCP/IP, 1 multi-user web browser support
- UDP upload port for update
- CommIF software
- Reformatted GPS output (GGA and GLL)
- Heading Input: NMEA 0183, SBS, Synchro, and no gyro mode
- Dimensions: 19" X 1.75". 1U rack space

For further information please contact:

### Cobham SATCOM Maritime Systems

U.S.A. Tel: +1 925-798-7979  
 Fax: +1 925-288-1420  
 Toll Free: +1-888-798-7979  
 E-mail: [satcom.concordsales@cobham.com](mailto:satcom.concordsales@cobham.com)

EUROPE Tel: +44 2380 671155  
 Fax: +44 2380 671166  
 E-mail: [satcom.southamptoneurosales@cobham.com](mailto:satcom.southamptoneurosales@cobham.com)

ASIA Tel: +65 6795-2205  
 Fax: +65 6515-6546  
 E-mail: [satcom.asiasales@cobham.com](mailto:satcom.asiasales@cobham.com)